AWARNING

Do not use the harness for anything other than its intended purpose in parasail activities.

Do not put waist strap around outside of life jacket.

Do not fit passenger in harness that is more than 1 size larger than they should be wearing.

Do not fly passenger if they do not fit harness.

Do not pull behind a vehicle or use for tethered flight.

Do not use for skydiving or base jumping.

Operate the harness in compliance with the manual and all instructions provided on or with this product.

Do not operate under the influence of alcohol or drugs.

Failure to comply with <u>all</u> instructions and manufacturer's recommendations could result in death or serious injury.

ANY QUESTIONS? DO NOT HESITATE TO CONTACT US:



1218 50th Avenue Plaza West Bradenton, Florida 34207 Tel: +1 941 753 4818 Fax: +1 941 755 9799 www.customchutes.com info@customchutes.com



Harness shoulder strap instructions





DO NOT USE THIS PRODUCT FOR ANY PURPOSE OTHER THAN ITS INTENDED PURPOSE IN PARASAIL ACTIVITY. ALL MANUFACTURER'S INSTRUCTIONS AND RECOMMENDATIONS MUST BE FOLLOWED. READ PRODUCT MANUAL PRIOR TO USE. FAILURE TO COMPLY WITH ALL INSTRUCTIONS AND RECOMMENDATIONS COULD RESULT IN DEATH OR SERIOUS INJURY



3 Strap sizes, Green for S - S/M, Black for M - L, Red for XL - XXL

Attaching shoulder straps



Attach shoulder straps by first connecting the straps to the back of the harness. Pass the tri-glide up through the receiver and lay flat on top.

S, S/M, M, L, XL, XXL with shoulder


straps attached.



Pull receiver to secure against hole. From underside pass up guard strap through receiver and tri-glide, pull tight. Secure down on Velcro

Attaching shoulder straps





Take a shoulder strap with a tri-glide on it, holding both parts of the strap pass tri-glide from the back through the receiver connected to the waist strap and lay flat on top.



Pull tight to secure, to adjust shoulder straps pull on loose end to tighten.

Putting on



Put on harness as normal and place shoulder straps over shoulders (do not cross them). Pull ends to tighten shoulder straps for comfort.









Then connect chest strap by passing tri-glide holding both parts of the strap, pass from the back through the receiver and lay flat on top. Pull tight to secure, to adjust strap pull on loose end to tighten.





Chest strap should be at breast height. To adjust slide the metal piece up and down to desired location. Then place lifejacket over the top.